

**OLA Energy**  
**lubricants**  
**product guide**



**Introduction**

**General overview**

**Commercial vehicle oils**

# Product Categories

# Passenger Vehicle Lubricants

## Passenger Vehicle Oils

### Engine

Accel FUSION Series

Accel ULTRA S

Accel XL Series

Accel XLD Series

### Motorcycle

MotoPower Series

## Commercial Vehicle Oils

### Engine

DeoMAX SYN

DeoMAX DM Series

### Hydraulic Applications

DeoMAX HD

### Super Tractor Oil Universal

Agrol Series

## Transmission Oils

### Automatic Transmission

ATF Series

### Manual Transmission

GearOil Series

Trans FD

Stratafluid

## Industrial Oils

### Hydraulic

Hydrol Series

Hydrol HTE Series

Hydrol M Series

### Enclosed Gear

Torqgear Series

### Circulating

Vacuolube Series

### Turbine

Hydrol Named Series

### Air Compressor

Glytech Series

### Heat Transfer

Thermic Oil

Process

Process Oil Series

## Marine Oils

Marinegard 12 Series

Marinegard 30,  
40 Series

Marinegard 70

Hydrol M Series

## Greases

Lubix SHC Series

Lubix XHP Series

Lubix EP Series

Names	Specifications	SAE Grade	Descriptions and Applications
-------	----------------	-----------	-------------------------------

Accel FUSION 5W-40	API SN /CF ACEA A3/B4-04 ACEA C3-10 MB 229.31 approved VW 502 00 VM 505 00 VW 505 01 approved BMW-LongLife-04 approved Porsche A 40 Ford WSS-M2C917A RN 0700/0710 Opel Dexos 2	5W-40	Synthetic engine oil for passenger and light duty diesel cars formulated with modern technology components and synthetic base oil offering excellent qualities
Accel FUSION V-Motion 5W-30	ACEA A3/B4-04 ACEA C3-08 VW 504 00 / 507 00 MB 229.51 BMW LL-04 PORSCHE C30	5W-30	Synthetic engine oil designed for gasoline and diesel engines found in the latest passenger cars and light vans
Accel ULTRA S 10W-40	API SN/CF ACEA A3/B4-10 MB 229.1 VW 501.01/505.00	10W-40	Semi-synthetic engine oil for passenger and light duty diesel cars formulated with modern technology components meeting the latest lubrication specifications
Accel XL10 20W-50	API SL/CF	20W-50	Premium multigrade oil for Gasoline engines that exceeds the latest standards required in all modern engines
Accel XLD10 15W-40	API CF-4 / SJ	15W-40	Premium multigrade oil for Diesel engines that exceeds the latest standards required in all modern engines
Accel XL8 20W-50	API SG/CF	20W-50	High performance engine oil for gasoline vehicles. Provides an excellent protection and engine cleanliness

# Passenger Vehicle Lubricants

Names	Specifications	SAE Grade	Descriptions and Applications
Accel XLD8 15W-40	API CF/SF	15W-40	High performance engine oil for gasoline vehicles. Provides an excellent protection and engine cleanliness
Accel XL5 SAE-30	API SG /CF	30	Monograde engine oil for use in car engines and commercial vehicles
Accel XL5 SAE-40	API SG /CF	40	Monograde engine oil for use in car engines and commercial vehicles
Accel XL5 SAE-50	API SG /CF	50	Monograde engine oil for use in car engines and commercial vehicles
MotoPower 2T	API TC JASO FA JASO FC		High performance two-stroke engine oil for use in motorcycles, snowmobiles and lean/fuel ratio chain saws. MotoPower 2 T is pre-diluted to ensure rapid mixing when added to fuel
MotoPower 4T	API SL /SG JASO MA/ MA-2	20W-50 15W-40	Mineral based 4-stroke motorcycle oil specially formulated to provide outstanding protection under severe high torque, high stress conditions

# Commercial Vehicle Lubricants

Names	Specifications	SAE Grade	Descriptions and Applications
DeoMAX SYN 5W-40	API CJ-4/CI-4 PLUS/ CI-4/SM ACEA E7-08; ACEA E9-08 MB 228.31; DDC PGOS 93K218 MAN 3275 VOLVO VDS-4; Renault RLD-3; Mack EO-O PP 07 Cummins CES 20081 Caterpillar ECF-2 / ECF-3 Deutz DQC III-05	5W-40	High performance synthetic engine oil (PAO) that provides outstanding protection against wear, corrosion and oxidation and reduces deposits and sludge build up to keep engines running reliably in all operating temperatures
DeoMAX DM12 15W-40	API CI-4/CH-4/CG-4/ CF-4/CF API SL/SJ ACEA E7/A3/B4 MB 228.3 (P), 229.1 MAN 3275 VOLVO VDS-3 MTU 2.0 MACK E O-M PLUS CUMMINS CES 20076/CES 20077/ CES 20078 CATER PILLAR ECF-1a RENAULT RLD-2 DETROIT DIESEL 93K215 DEUTZ DQL III-05 GLOBAL DHD-1	15W-40	Premium high performance diesel engine oil for variety of classic and modern engines, high output engines, including those fitted with exhaust gas (EGR) working under severe conditions
DeoMAX DM10 15W-40	API CH-4/CG-4/CF-4/ CF API SL / SJ ACEA E7/A3/B4 MB 228.3 (P), 229.1 MAN 3275 VOLVO VDS -2 MTU 2.0 MACK EO-M PLUS CUMMINS CES 20076 / CSE 20077 CATERPILLAR ECF-1A RENAULT RLD-2 DEUTZ DQL II-05	15W-40	High performance oil for diesel engine working in severe conditions . Recommended for variety of engines: on-highway light and heavy trucking and off highway engines: construction, mining, quarrying, and agriculture

# Commercial Vehicle Lubricants

Names	Specifications	SAE Grade	Descriptions and Applications
DeoMAX SYN 5W-40	API CJ-4/CI-4 PLUS/CI-4/SM ACEA E7-08; ACEA E9-08 MB 228.31; DDC PGOS 93K218 MAN 3275 VOLVO VDS-4; Renault RLD-3; Mack EO-O PP 07 Cummins CES 20081 Caterpillar ECF-2 / ECF-3 Deutz DQC III-05	5W-40	High performance synthetic engine oil (PAO) that provides outstanding protection against wear, corrosion and oxidation and reduces deposits and sludge build up to keep engines running reliably in all operating temperatures
DeoMAX LD 10W-40	API SN /CF ACEA E7-16/ACEA E4-2016 MB Approval 228.5 MAN M 3277 MTU type 3 Volvo VDS-3 Renault RLD/RDL-2 MACK EO-N Cummins CES 20077/20078 Detuz DQC IV-10	10W-40	Synthetic lubricant formulated with high quality synthetic base stock and an advanced additive package to offer the best performance in use in modern heavy-duty diesel engines for longer drain intervals. Wide range of trucking and transportation application. Heavy duty diesel engines under severe operating condition. Naturally aspirated and turbo-charged diesel-powered equipment. Industrial equipment
DeoMAX DM12 15W-40	API CI-4/CH-4/CG-4/CF-4/CF API SL/SJ ACEA E7/A3/B4 MB 228.3 (P), 229.1 MAN 3275 VOLVO VDS-3 MTU 2.0 MACK E O-M PLUS CUMMINS CES 20076/CES 20077/ CES 20078 CATERPILLAR ECF-1a RENAULT RLD-2 DETROIT DIESEL 93K215 DEUTZ DQL III-05 GLOBAL DHD-1	15W-40	Premium high performance diesel engine oil for variety of classic and modern engines, high output engines, including those fitted with exhaust gas (EGR) working under severe conditions

# Commercial Vehicle Lubricants

Names	Specifications	SAE Grade	Descriptions and Applications
DeoMAX DM 12 EXTRA 15W-40	ACEA E7-16 (2016) MB-Approval 228.3 Volvo VDS-3 Renault Truck RLD/RDL-2 Cummins CES 20078 Global DHS-1 API-4 MAN M 3275 MACK EO-N CUMMINS CES 20076 CAT ECF-2 Deutz DQC 111-10 API SL MTU Type 2 Mack EO-M plus Cummins CES 20077 CAT ECF-1-a Detroit DDC 93K215	15W-40	Premium performance multigrade engine oil formulated for diesel engines and recommended by European and American manufacturers. Ensures an excellent performance in severe conditions. Limits wear on start-up through good pumpability and excellent flow. Reduce engine wear and bore Polishing. Reduces fuel consumption and maintenance costs.
DeoMAX DM10 15W-40	API CH-4/CG-4 /CF-4/CF API SL / SJ ACEA E7/A3/B4 MB 228.3 (P), 229.1 MAN 3275 VOLVO VDS -2 MTU 2.0 MACK EO-M PLUS CUMMINS CES 20076 / CSE 20077 CATERPILLAR ECF-1a RENAULT RLD-2 DEUTZ DQL II-05	15W-40	High performance oil for diesel engine working in severe conditions. Recommended for variety of engines: on-highway light and heavy trucking and off highway engines: construction, mining, quarrying, and agriculture
DeoMAX DM8 15W-40	API CG-4 /CF-4/CF API SL / SJ ACEA E3/A3/B3 MB 228.3 MAN 3275 VOLVO VDS MTU 2.0 RENAULT RD/RGD DEUTZ DQL II-05	15W-40	High performance oil for diesel engine working in severe conditions. Recommended for variety of engines: on-highway light and heavy trucking and off highway engines: construction, mining, quarrying, and agriculture



# Commercial Vehicle Lubricants

Names	Specifications	SAE Grade	Descriptions and Applications
-------	----------------	-----------	-------------------------------

DeoMAX DM7 15W-40	API CF-4/SG MB 228.0/228.1 ACEA E2 MAN 270/271 VOLVO VDS MTU 1.0 DEUTZ DQC1-05	15W-40	High technology oil and particularly efficient in modern diesel
DeoMAX DM 5 SAE-30	API CF	30	High performance monograde oils for turbocharged diesel engines and natural aspirated working under severe operating conditions such as on and off - highways segments
DeoMAX DM 5 SAE-40	API CF	40	High performance monograde for turbocharged diesel engines and natural aspirated working under severe operating conditions such as on and off - highways segments
DeoMAX DM 5 SAE-50	API CF	50	High performance monograde oils for turbocharged diesel engines and natural aspirated working under severe operating conditions such as on and off - highways segments
DeoMAX HD 10W	API CF	10W	High performance hydraulic oil that contains an effective balance of ashless dispersant and metallic detergent combined with inhibitors to control corrosion, oxidation, wear and rust. Used in a wide range of hydraulic equipment



# Commercial Vehicle Lubricants

Names	Specifications	SAE Grade	Descriptions and Applications
-------	----------------	-----------	-------------------------------

Agrol Super 15W-40	API CG-4/SF ACEA E3 API GL-4 CATERPILLAR TO-2 ALLISON C-4 ZF TE-ML 06A/B/C/07B FORD M2C 134D/159B/C NEW HOLLAND 82009201/2/3 CASE NEW HOLLAND MAT M1135/1139/1143/1144/1145 3525/3526 JOHN DEERE J27/J20C	15W-40	High performance STOU working in severe conditions recommended for use in crankcase of diesel and four stroke gasoline engines, Hydraulics, transmissions, wet brakes, power take offs, hydrostatics and power steering
Agrol 15W-40	MASSEY FERGUSON CMS API CD API GL-4 CAT TO-2	15W-40	STOU working in severe conditions recommended for use in crankcase of diesel and four stroke gasoline engines, hydraulics, transmissions, wet brakes, power take offs, hydrostatics and power steering



# Transmission Oils

Names	Specifications	Descriptions and Applications
-------	----------------	-------------------------------

ATF TASA	FORD TASA	Fluid for automatic transmissions vehicles. Also used as hydraulic
ATF II D	GM DEXRON IID	fluid in unique applications Fluid for automatic transmissions vehicles specifying Dexron II D. Also used as hydraulic fluid in unique applications
ATF III G	DEXRON III G GM DIIIG ZF TE-ML 14A, 03D, 04D, 17C, 09 VOITHH55.6335. XX MAN 339 TYPE V1/Z1 MB 236.9 VOLVO STD 1273.4 TRANSMISSION OIL 97340 VOLVO STD 1273.41 TRANSMISSION OIL 97341 FORD M (QUALITY) ALLISON C-4 FORD TASA	High performance fluid for automatic transmissions vehicles specifying Dexron III G. Also used as hydraulic fluid in unique applications



# Transmission Oils

Names	Specifications	SAE Grade	Descriptions and Applications
-------	----------------	-----------	-------------------------------

GearOil BV 75W-80	API GL-5	75W-80	Premium automotive gear lubricant especially for Hypoid axles, enclosed gearboxes and manual gearboxes demanding performances defined by API GL-5 in 75W-80 grade
GearOil LS 85W-90	API GL-5 ZF TE-ML 05C ZF TE-ML 12C ZF TE-ML 16E ZF TE-ML 21C ARVIN MERITORAXLES	85W-90	Premium automotive gear lubricants formulated from high quality base oils and an optimum balanced additive system specifically for limited-slip differentials
GearOil XHD 80W-90	API GL-5	80W-90	Premium automotive gear ubricant that protects commercial axles and final drives where extreme pressures and shock loading are expected
GearOil XHD 85W-140	API GL-5	85W-140	Premium automotive gear lubricant that protects commercial axles and final drives where extreme pressures and
GearOil HD 80W-90	API GL4	80W-90	shock loading are expected Automotive gear lubricants for commercial axles and final drives where extreme pressures and shock loading are expected
GearOil HD 85W-140	API GL-4	85W-140	Automotive gear lubricants for commercial axles and final drives where extreme pressures and shock loading are expected



# Transmission Oils

Names	Specifications	Descriptions and Applications
Trans FD 10W	Cat TO-4 Allison C-4	High performance transmission and drive-train lubricants engineered to meet the specifications required by Caterpillar TO-4
Trans FD 30	Cat TO-4 Allison C-4	High performance transmission and drive-train lubricants engineered to meet the specifications required by Caterpillar TO-4
Trans FD 50	Cat TO-4 Allison C-4	High performance transmission and drive-train lubricants engineered to meet the specifications required by Caterpillar TO-4
Stratafluid 55	API GL-4 Case New Holland CNH MAT 3525/ C NH MAT 3505/MAT 3509 Ford ESN-M2C134-D/ ESN-M2C86-C/ ESN-M2C86-B CASE MS 1210 / MS 1207 VCE WB 101 Allison C-4 John Deere JDM J20C/ JDM J20D FNHA-2-C-200.00 Kubota UDT Fluid Caterpillar TO-2 Massey Ferguson CMS M1135/ CMS M1145/ CMS M1141/ CMS M1143 ZF TE-ML 05F/TE-ML 03E/ TE-ML 06K/TE-ML 17E	Extra high performance multipurpose tractor lubricant engineered to meet and exceed transmission and hydraulic fluid requirements



# Industrial Oils

Names	Specifications	ISO Grade	Descriptions and Applications
Hydrol M Series	DIN 51524 Part 3 Eaton	32	High performance anti-wear hydraulic oils engineered for wide temperature range applications
	Vickers M-2950-S Eaton	46	
	Vickers I-286-S Cincinnati	68	
	Machine P- 68 Cincinnati	100	
Hydrol HTE Series	Machine P- 69 Cincinnati	150	Premium quality anti-wear hydraulic oils intended for industrial and mobile service applications where anti-wear lubricants are required
	Machine P- 70 Parker		
	Hannifin France HF-0		
	Approved (Hybrid T6H20C Pump Test)		
	ISO 11158 L- HV		
Hydrol Series	Cincinnati Machine P- 68/P-69/P-70	32	Premium quality anti-wear hydraulic oils intended for industrial and mobile service applications where anti-wear lubricants are required
	approved GM LS-2 JCMAS	46	
	HK U.S. Steel 127; 136	68	
	Bosh Rexroth Parker	100	
Hydrol Series	Hannifin France HF-0 DIN 51524 Part 2 Eaton Vickers M-2950-S	150	Premium quality anti-wear hydraulic oils intended for industrial and mobile service applications where anti-wear lubricants are required
	ISO 11158: HM		
	DIN 51524 Part 2 (HLP)	32	
	M-2950-S	46	
Hydrol Series	ISO 11158: HM	68	Premium quality anti-wear hydraulic oils intended for industrial and mobile service applications where anti-wear lubricants are required
		100	
		150	

# Industrial Oils

## Names

## Specifications

## ISO Grade

## Descriptions and Applications

Hydrol Named	DIN 51515 p.1	32	Premium Zinc-Free turbine and circulating lubricants recognized for their high quality and reliability
	(L-TD), p.2 (L-TG)	46	
	MIL-L-17672D US	68	
	Steel 120		
	Siemens TLV		
TorqGear Series	9013 04 BS 489		high quality oils for circulating or splash systems of enclosed gears. Excellent extreme pressure and high load properties that give exceptional protection against wear. Formulated from high refined mineral oils and selected additive system to provide strong oxidation resistance and protection against corrosion and rust even in sea water, in addition, these oils have good water separation and anti-foam properties
	General Electric		
	GEK 32568 A/C		
	CEGB 207001		
	Brown Boveri		
	HTGD 90117		
	Alsthom HTGD		
	90 117 V0001 S		
	Westinghouse		
	Electric Corp		
Turbine Oil Spec			
Glytech Series	DIN 51506 VD-L	32	High quality lubricants intended for use in air compressors, recommended for use in all types of rotary screw, rotary vane and reciprocating air compressors
		46	
		68	
		100	
		150	

# Industrial Oils

## Names

## Specifications

## ISO Grade

## Descriptions and Applications

Transformer Oil II	IEC 60296 –U-2012-02 Edition 4.0 standard -2 Essais de Corrosion ASTM D1275B/CIGRE		Uninhibited insulating fluid, for use in electrical systems where rapid heat transmission and high oxidation stability are required. Highly refined mineral oil with natural low pour point characteristics
Circ Oil		100	High performance circulating oils for use in a wide range of industrial equipment such as heavy duty circulating oils designed for the demands of No-Twist Rod mills
		320	
Thermic Oil		32	High quality heat transfer oil for use in closed indirect heating installations
Process Oil		32	Paraffinic process oils with a light colorant good color stability. Gives improved resiliency, good extrudability, reduced heat build-up, and better low temperature flexibility
		46	
		68	
		100	
		150	
		220	
	320		
	460		





# Marine Oil

Names	Specifications	SAE Grade	Descriptions and Applications
-------	----------------	-----------	-------------------------------

MarineGard HSD 15W-40	API CI-4/ACEA E7 MAN 3275 VOLVO VDS-3 MACK E O-M PLUS CUMMINS CES 20076/77/78 Caterpillar ECF-1a DETROIT DIESEL 93K215 DEUTZ DQL III-05 GLOBAL DHD-1		High performance diesel engine oil for MTO/MGO engines
MarineGard 312	API CF TBN12	30	High performance diesel engine oil for use in trunk piston engines operating on low sulphur distillate in marine and industrial applications
MarineGard 412	API CF TBN12	40	
MarineGard 330	API CF TBN30	30	High performance diesel engine oil, with high total basic number (TBN 30), for use in trunk piston engines operating on high sulphur content distillates and heavy fuel oils in marine and industrial applications
MarineGard 430	API CF TBN30	40	
MarineGard 340	API CF TBN40	30	High performance diesel engine oil, with high total basic number (TBN 40), for use in trunk piston engines operating on high sulphur content distillates and heavy fuel oils in marine and industrial applications
MarineGard 440	API CF TBN40	40	
MarineGard 450	API CF TBN50	40	
MarineGardM 450	API CF TBN17 ZINC FREE	40	Zinc Free diesel marine engine Oil. TBN 17
MarineGard 70	API CF TBN70	50	High quality oil cylinder for marine diesel engine. Offers maximum protection against adhesive and corrosive wear at high temperatures and pressures of modern engines



# Grease

Names	BO Viscosity Grade	NLGI Grade	Descriptions and Applications
-------	--------------------	------------	-------------------------------

Lubix Calcigrease	150	1	Calcium Grease with Extreme Pressure properties
Lubix EP 0	150	0	Lithium Grease with Extreme Pressure properties
Lubix EP 1	150	1	
Lubix EP 2	150	2	
Lubix EP 3	150	3	
Lubix SHC 100	100	2	Extreme Pressure Grease manufactured with Synthetic Base Oil and Lithium Complex thickener for Superior performance
Lubix SHC 220	220	2	
Lubix SHC 460	460	1,5	
Lubix XHP 220	220	2	Lithium Complex Grease with Extreme Pressure properties
Lubix XHP 320 Special	320	2	High Performance Lithium Complex Grease with Extreme Pressure properties and anti-wear (with molybdenum disulfide)
Lubix XHP 460 Special	460	2	

**Operational HQ and  
Correspondence Address**  
**OLA Energy** Services DMCC  
12th Floor, JBC5, Cluster W,  
Jumeirah Lake Towers,  
Dubai, UAE  
P.O. Box 488202  
Tel : +971 4 429 5000  
Fax : +971 4 429 5051